# **SPECIFICATIONS**

(RoHS Compliant)


**Model Number**: ST12Z3

**Part Number:** 19039067A

**SPEC Number:** 26007487A03



## **Mechanical Drawing:**



### **Motor:**

Nominal Voltage = 12 vdc
Operating Voltage Range = 6 - 14 vdc
Nominal Running Current = 0.520 amps
Max. Locked Rotor Current = 2.100 amps
Running Power = 6.20 watts
Average Speed = 4700 RPM

 $\begin{array}{ll} \text{Bearings} & = \text{Ball} \\ \text{Rated Air Flow} & = 45 \text{ CFM} \end{array}$ 

Rated Air Pressure =  $92 \text{ Pa} (0.37 \text{ in H}_2\text{O})$ 

Acoustic: = 51.5 dBA

#### **Construction:**

Venturi: Plastic, Black, UL 94V-0 Propeller: Plastic, Black, UL 94V-0

# **Life Expectancy:**

This fan is designed for continuous duty life of 62,400

hours at 40°C.

### **Additional Features:**

Brushless DC Motor

Electronic Locked Rotor Protection

Feb. 26, 2013

Polarity Protected

**Automatic Restart Capability** 

Operating Temperature: -10°C to 70°C Storage Temperature: -40°C to 85°C

#### **Termination:**

12" Lead wires, 22AWG, UL 1061

Red – Power Black - Return

# **Agencies:**

UL, CE